Additional Crafco Products

Crack and Joint Sealant

Crafco formulates a wide variety of joint and crack sealants that meet and exceed Federal and State specifications. All Crafco Sealants are guaranteed from start to finish. Crafco has the broadest line of sealant in the industry making Crafco your "one-stop shop" for all your sealant requirements. With four manufacturing facilities across the United States Crafco guarantees efficient and timely shipping, supplying customers with product on-time, every time.

Pavement Joint Adhesive

Crafco Joint Adhesive is a unique polymerized asphalt product that is applied to the longitudinal cold joint interface between hot mix asphalt paving passes. A thin layer applied to the interface bonds less dense or segregated material together and waterproofs the joint apex. which prevents raveling and crack formation.

Spray Injection Patcher

The Crafco Spray Injection Patchers are the most cost effective repair systems for pothole repair today. Distressed pavements are cleaned, tack coated, and filled in minutes by one continuous operation. This system can be used year round and is an ideal addition to your pavement preservation system.

PolyPatch

Crafco PolyPatch is a unique blend of polymer modified asphalt and select aggregate specifically designed for repairing pavement distresses too large for crack sealing and too small for re-paving.

Your local Crafco representative:

Loop Sealant

Crafco Loop Sealant is widely accepted for use in sealing traffic intersection loop detectors. Crafco Loop Sealant provides 100% encapsulation of the sensor wires. Applicator equipment also available.

Marker Adhesive

Both Crafco Standard and Flexible Marker Adhesive materials assure marker buttons and lane reflectors stay where they are placed. Standard and Flexible Marker Adhesives are hot-applied bituminous based products that are accepted worldwide. Applicator equipment also available.

Roofing & Waterproofing

Crafco supplies a variety of bulk and packaged asphalt material used in the production of asphalt shingles, in the construction of built up roofing systems and for structural waterproofing. Applicator equipment also available

TechCrete

Crafco TechCrete is the flexible solution for concrete repair and is a proven hot pour repair that is different from all conventional rigid repair methods. Once in place TechCrete will move with the pavement and will not de-bond or crack. With CrafcoTechCrete it's a one time fix





ASPHALT COLD PATCH Permanent Asphalt Repair

The year-round - All Season -**High Performance Cold Patch**

Permanent Cold Patch Repair Paves the Way

WWW.Cratco.com For more information on Crafco products contact your local Crafco Distributor or call:

00.528.8242

420 N. Roosevelt Ave. Chandler, Arizona 85226, USA Phone 602-276-0406 Fax: 480-961-0513




Excellent results in summer heat, bitter cold, or wet conditions!

Whether it is repairing utility cuts or patching that reoccurring pothole, HP Asphalt Cold Patch is rapidly becoming the material of choice. HP Asphalt Cold Patch is approved as a high performance patching material in most states and other user agencies within the United States. HP Asphalt Cold **Patch** is specifically formulated for the wide-ranging temperature and climate of our area. HPAsphalt Cold Patch is permanent, fully guaranteed against any failure, and most important, does the job right the first time.

Quick facts:

- · Works in all weather conditions, wet, cold or hot.
- Approved, used and tested by utilities and states nationwide.
- Easy to use bags prevent waste and saves money.
- No mixing, mechanical compaction or tacking. •
- Cost effective with no messy clean-up or time • constraints.
- Permanently adheres to asphalt, concrete, or steel. •
- · Perfect for bridge, drain, utility cuts, and cutter work.
- · Patch will not release, eliminates milling before repaving.
- Proven non-hazardous.
- Biodegradable, non-toxic. •
- All season, use in summer or winter. •



Clear pothole of loose debris and pour HP into the hole or utility cut.

Spread HP in two inch (2") increments, outward to each edge of the area to be repaired.





Compact or tamp into place. *Open to traffic* immediately. It's that simple!

50lb / 22.7kg Bag Usage Guide

Hole Dimension in Feet	Depth in Inches	Total Bags Needed
2´ X 2´	2″	2
2´ X 2´	3″	3
2´ X 2´	4″	4
3´X 4´	2″	6
3´X 5´	2″	7
3´ X 3´	4″	8

HP Asphalt Cold Patch is specifically engineered to remain somewhat pliable following application. This allows our product to eliminate small voids and crevices through continual compaction. Should vou require faster set up times, a light sprinkling of Portland cement or mortar dust prior to compaction will help to speed the curing process.