

Crack Preparation

Crafco Pavement Cutter/Router



CRAFCOTM
AN **ERGONE** COMPANY **INC**

"Pavement Preservation Products"

Random cracks stay sealed 50% longer when they are routed with the Crafcro Model 200 Pavement Cutter and sealed with a quality sealant. (SHRP H.106 Report)

31134 Steel Cutter



Place in line with six spacers on each side. The cut will be approximately 1/2 inch wide. Use on AC pavement or PCCP. Some spalling can be expected.

31145 Wide Hub Cutters



The wide hub and smaller arbor reduces cutter "wobble" providing a cleaner pavement cut which improves the sealant bond to the crack sidewall. Provides 1/2 inch to 3/4 inch cut.

31136-7 Carbide Cutters



Place six spacers on each side for a 1/2 inch wide cut. Stack two cutters side by side with three spacers on each side, or stagger in a 2-1-2-1-2-1 configuration for a 1.3 inch wide cut. You can also use three cutters side-by-side for a two inch wide cut. These cutters can be used on AC pavement or PCCP.

31138 - 6 1/2" Carbide Cutters



These cutters are the same as the 31136-7 cutter except they have an increased cut depth up to two inches. Three cutters are evenly spaced on the cutter head leaving every other pin empty.

31114 - Cutter Pins

Crafcro cutter pins are ultra hard on the outside for wear resistance and flexible on the inside.


Dual stage air cleaner protects engine from premature internal engine wear.

Air indicator alerts operator when filter maintenance is needed.

Unbreakable non-metalized gas tank increases tank durability and reduces chance for gas leaks.

Stabilizer Foot for changing cutters.

Rock deflector



Routed Crack enhances sealant adhesion and increases crack seal longevity.

Clutch Operated: An electric clutch is mounted on the pavement cutter to stop and start the cutter head on demand.

25hp Engine


Electric activated depth control provides precision cutter depth.

Sealed Wheel Bearings

The Crafcro Model 200 Pavement Cutter has been the industry standard for over thirty years. There is no other Pavement Cutter that can match the quality, reliability, long term performance and features of the Crafcro Model 200. Its lightweight mobile design, unique center of axis and cutter head alignment enables it to produce unmatched crack following accuracy. There is no better way to effectively and efficiently create sealant crack reservoirs than with the Crafcro Model 200 Pavement Cutter, the most popular Pavement Cutter throughout the world.

Over 30 years of proven performance • Most comprehensive service coverage

Crack Saw Attachment Option



The Crafcro Crack Saw Attachment is designed to convert the Crafcro Model 200 Pavement Cutter into a joint and random crack saw for use on concrete and asphalt. Conversion takes less than one hour. Diamond or abrasive blades (not included) may be used wet or dry. All parts necessary to transform the Pavement Cutter into a saw (belts, bearings, shafts, hoods, and brackets) are included.

Self Propelled Option



The Model 200 Pavement Cutter Self Propel option will move the cutter uphill, up inclines (road crowns) and from crack to crack effortlessly. Simply engage the wheel drive power whenever it is needed. The self-propelled option greatly increases productivity and decreases operator fatigue.

U.S. Patent Number 6102022